

CARR North America Product Specification Sheet

CARRFLEX® CFX30 - SUPER HEAVY WEIGHT POLYURETHANE DOUBLE COATED POLYAMIDE WITH FLAME RETARDANT COATING, ANTI-BACTERIAL, FLUID PROOF

| Specifications (Testing Standard) | |
|---------------------------------------|---------------------------------|
| Weight | 8.99 oz/yd ² +/-6% |
| Available Width(s) | 47.2 / 59 / 86.6 in |
| Composition | 46% Polyamide/54% PU FR Coating |
| Tensile Strength (ISO 13934-1) Warp | >135 lbf |
| Tensile Strength (ISO 13934-1) Weft | >56 lbf |
| Tearing Strength (ISO 13937-1) Warp | >9 lbf |
| Tearing Strength (ISO 13937-1) Weft | >7.9 lbf |
| Breaking Extension (ISO 13934-1) Warp | 80% |
| Breaking Extension (ISO 13934-1) Weft | 180% |
| Waterproofness (ISO 20811) | > 3000 mm |
| Wash Temperature Maximum | 167° F |
| Dry Cleaning | OK |
| Fire Standard | 16CFR1632.6, CAL117 |

CARRFLEX® CFX-30 is a specially manufactured product on which both sides are coated with a heavy polyurethane designed to resist a wide range of chemical cleaners. The unique feature of this product is the consistency of performance of both coated sides. Both weldability and coating adhesion are consistent from side to side. In applications where enhanced surface durability and tear resistance is required, CFX-30 is an excellent choice.



P.O. Box 988
 540 Kenneth Welch Drive
 Lakeville, MA 02347
www.CarrNorthAmerica.com
 Toll Free: 800.875.5677
 Email: info@CarrNorthAmerica.com